

# **AgroLume**<sup>®</sup> better business sense

# The AgroLume SYSTEM

HARSH POULTRY ENVIRONMENT

#### **Poultry Lighting**

AGROLUME offers a complete system solution for Poultry lighting comprising of 5 star IP66 LED Bulb + IP66 Cords & Connectors + Mosfet Dimmer-Controller.

#### **Lighting Science**

Technology developed through active research in collaboration with leading American universities. Continuous innovation and development with academic and Industry experts

#### **Proven Results**

The largest selling LED Brand in North America Poultry Industry with over 3 Million successful installations



The most energy efficient, rugged, long-

for The Harsh Poultry Industry condition

lasting Lighting system designed specially

#### **Overdrive Dimmer Controller**

- Smooth Flicker Free Dimming
- Dual Output zone

Designed for

NOW IN INDIA

- Independent Lighting Schedule
- Programmable Auto Lighting Control
- Dimming curve programme



#### Harsh-environment-resistant connector


- Lighting Cord Sets
- Offers easy relocation
- Protection from Dust, Moisture
- 100 feet(30 meter), 18 AWG with water proof flexible sockets



Profitability

### The Lighting 5 Star BEE Bulb \* 120lm/Watt \* Flicker Free Dimming IP66 rated

- Advanced dimming IC for uniform, Flicker free dimming.
- Advanced LED Chip yielding over 120 Lumens per Watt.
- Unique optimized optical design for full utilization of floor light.
- No Fins design Easy to clean.
- First BEE 5 star rated dimmable LED bulb for poultry application.
- Low on maintenance cost and 25,000 hours life.
- Suitable for Wet Location (IP66) rated.



Watt	lm/w	Lumen	ССТ	Life
12W	120	1440 lm	5000K	25,000 hours


# **The Controller** Digital MOSFET DIMMER + CONTROLLER


- Flicker free dimming up to 1%.
- 3 Programs Master, manual and Slave mode for quick and easy programming.
  - Master mode with programmable auto lighting control.

  - Manual mode for keypad control.
    Slave mode with 0 10V DC analog voltage control.
- Digital short circuit safety protection, Over 3KV surge protection.
- Integrated 1.3" OLED Display, Replaceable output fuses.



Rating	12W/DIM LED Bulb	
2 X 10 Amp	2 X 100 = 200	





- Nickel plated, Water-resistant Holder.
- Calibrated spacing for uniform light distribution.
- Expandable water proof connector Sockets.
- Insignificant voltage drop over extended length usage.
- 4 Inch suspended E26 socket to keep the lamp straight during usage.

Len	gth	No. of Sockets	Wire Gauge	Max Wattage	Space
100	) ft	10	18AWG	1440W / 12Amp	10 ft

Overdrive Electronics Pvt. Ltd | Noida Unit/HO: C121, Hosiery Complex, Phase 2 Ext, Noida 201305 UP India |Phone: + 91 120 4133600 | Mail: info@overdriveasia.com | Website: www.overdriveasia.com